OPERATING / MAINTENANCE INSTRUCTIONS

FL7, 4 Operative Operation - Trench RB Cover Removal and Replacement

Issue: 15/04/2021

PLEASE HAND TO SITE OPERATOR

WARNING

The handles must be used at all times to remove/ replace the cover. Lifting and replacing the cover is a minimum two person operation. Do not insert any levering device between the cover and frame. Do not paint the tread pattern surface as this may compromise the anti-slip properties.





BRELIT

REMOVAL - UOB NBIF TRENCH COVERS



Remove all the restraining bolt plugs and using the FM-A-KEY (T Bar Allen Key), the restraining bolts.



Insert handles at 90° from cover length, turn clockwise.



Simultaneously pull the cover upwards.

REPLACEMENT/ MAINTENANCE - UOB NBIF TRENCH COVERS



Clear and clean the frame or rebate, particularly the seating face. Inspect for damage.



Lower the cover into position.



Clean the cover using only warm water and standard cleaning detergents. Inspect for damage. Frequency depends on use and the working environment but it is recommended that cleaning and inspection are carried out at least once every 6 months. It is recommended that spillages are clean up immediately



Insert handles at 90° from cover length, turn clockwise.

Cover Load Rating

The covers are badged/Marked B125, which means they comply with the loading requirements of BS EN 124. This standard identifies the point load on the B125 covers as a concentrated point load of 125kN on a footprint of 250 mm diameter test disc so this is used as the wheel footprint/point load.

ΝΟΤΕ

If the covers become damaged due to impact they must be repaired to prevent long-term damage to the internal structure.

Contact Fibrelite's Technical Department

Using the FM-A-KEY (T Bar Allen Key), replace the all the restraining bolts and the restraining bolt plugs.

We've got you covered

UK Office: T: + 44 (0) 1756 799 773 F: + 44 (0) 1756 799 539, E: enquiries@fibrelite.com F: + 1 (800) 421 3297, E: enquiries@fibrelite.com F: + 603-7846 7788, E: enquiries@fibrelite.com

USA Office: T: + 1 800 422 2525

Malaysia Office: T: + 603-7847 1888