



FUELLING | WHAT'S NEXT

FIBRELITE 

S17 GRP Composite Tank Sump

Liquid-Tight | Vacuum-Testable | Fit-And-Forget

OPW 
a **DOVER** company

www.fibrelite.com

DEFINING | WHAT'S NEXT

The Fibrelite S17 GRP Composite Tank Sump

Liquid-Tight | Vacuum-Testable | Fit-And-Forget

The only truly liquid-tight option on the market, Fibrelite sumps are manufactured using the latest in GRP technology, and allow vacuum testing, during and after installation.

Easy Installation. Fit and Forget

Fibrelite manufactures high-quality one-piece moulded, GRP components with a smooth surface for easy installation of entry boots.

Key Benefits

- Liquid-tight
- Withstands high groundwater pressure
- Can be buried up to 3m (10') deep
- Anti-static surface
- The sump's smooth walls allow easy installation of pipe & cable entry sealkits, and provide a secure seal (when used with Fibrelite sealkits)
- Vacuum testable during and after installation
- Designed to create the maximum possible space for maintenance teams and installers to work
- Capable of accommodating dual manway lids where required
- Suitable for 3HP, 5HP or twin 1.5HP submersible pumps
- Available with collar ring or flanged base connection
- Collar ring base connection sumps are stackable, reducing shipping costs
- Guaranteed uniform 6mm (1/4") wall thickness
- Compatible with E15 & B15
- Corrosion resistant
- Suitable for use in high (and low) temperatures (-50°C/120°F to 50°C/120°F)

Item Code	Description
S17-3100	1.7m dia chamber with a bolted base, corbel, non structural internal lid, skirt, 1020mm dia black C250 cover with frame
S17-3100-D400	1.7m dia chamber with a bolted base, corbel, non structural internal lid, skirt, 1020mm dia black D400 cover with frame
S17-3100-CD	1.7m dia chamber with a bolted base, corbel, non-structural internal lid with central port, skirt, 1020mm dia black C250 cover with central sealed dip port with frame
S17-3100-CD-D400	1.7m dia chamber with a bolted base, corbel, non-structural internal lid with central port, skirt, 1020mm dia black D400 cover with central sealed dip port with frame
S17CRS-3100	1.7m dia stackable chamber with collar ring base, corbel, non-structural internal lid, skirt, 1020mm dia black C250 cover with frame
S17CRS-3100-D400	1.7m dia stackable chamber with collar ring base, corbel, non-structural internal lid, skirt, 1020mm dia black D400 cover with frame
S17CRS-3100-CD	1.7m dia stackable chamber with collar ring base, corbel, non-structural internal lid with central port, skirt, 1020mm dia black C250 cover with central sealed port with frame
S17CRS-3100-CD-D400	1.7m dia stackable chamber with collar ring base, corbel, non-structural internal lid with central port, skirt, 1020mm dia black D400 cover with central sealed port with frame
S17CRS-3100-BS	1.7m dia stackable chamber with collar ring base, corbel, non-structural internal lid
S17CRS-3100-CD-BS	1.7m dia. stackable chamber with collar ring base, corbel, non-structural internal lid with central port
FL100-SK300	300mm deep skirt to fit FL100
FL100-C250	1020mm dia. flat sealed black cover with frame, C250 load rating
FL100-D400	1020mm dia. flat sealed black cover with frame, D400 load rating
S17CRS-TC	S17CRS GRP tank collar

The Fibrelite sump range includes options for every type of tank connection. Visit the website for more information.



OPW EMEA Headquarters

Snaygill Industrial Estate, Keighley Road, Skipton, BD23 2QR, UK. Phone: +44 (0) 1756 799 773

OPW Sweden AB

Fabriksgatan 3, Kungsor 73636, Sweden. Phone: +46 (0) 227 422 00

enquiries@fibrelite.com