

OPW Simplifies BP Site Construction with New Fibrelite Sump and KPS Piping



The unique offset sump/corbel arrangement allows for bi-lateral pipe exits



All integrated KPS fittings weld both pipe walls simultaneously

**Project Overview**

BP approached OPW to provide a simple fill solution for a selection of their UK sites. In response, OPW developed a new range of Fibrelite GRP below ground remote fill systems.



Fibrelite's below ground remote fill systems with factory fitted/tested dual contained and conductive KPS pipework



Below ground remote fill systems incorporating a sump and offset corbel with alternate pipe exit positions

**Problem**

Due to site layout constraints, BP required a below ground remote fill with opposing pipe exit positions to ensure consistent fill layouts for tanker deliveries and simplify the installation reducing installation time and costs. Consideration was also given to the most efficient petrol pipework option.

**Solution**

OPW developed their existing range of Fibrelite below ground remote fill systems to incorporate a sump and offset corbel with alternate pipe exit positions in line with BP's requirements. The new sump and corbel utilised some items from the existing product range to deliver a unique while cost effective solution. This new product was made available in line with the start of the new construction programme.

The new below ground remote fill systems are factory fitted with dual contained KPS pipework for the fills and single wall for the stage 1 vapour line. Systems are fabricated in accordance with the supplied fuels layout drawing. Pipework is terminated above a secondary contained spill container with BP specified fill caps/adaptors and vapour recovery unit.

This environmentally friendly system is supplied ready to go with the earth bonding pre-fitted and both the pipework and dual contained GRP containment system factory tested prior to shipment. Once the systems are positioned on site the pipe contractor simply makes a fusion weld connection to the pipe tails on the outside of the sump.

Installer friendly KPS petrol piping was used to connect the remote fill sumps to petrol tanks and dispenser sumps. Where connections are required, compact KPS fittings weld both walls of a double wall pipe simultaneously, reducing installation time. Conductive double wall piping ensures safety in the eventuality of sparks or leaks.



The fully conductive below ground remote fill systems are supplied with a non-slip working platform for the tanker driver to stand on



Factory fitted with dual contained KPS pipework for fills and single wall for stage 1 vapour line



New sump and corbel utilised some items from existing product range to deliver a unique while cost effective solution

## Results

The new Fibrelite remote fill sump systems are now being specified for a number of BP's UK sites. These systems ensure consistent fill layouts for tanker drivers which together with KPS piping enables faster, more efficient site construction, reducing cost while creating a safe sealed system of the highest standard available.

**For more information on Fibrelite's product range please contact us:**

**UK Office:**

Tel: +44 (0) 1756 799 773  
Email: [enquiries@fibrelite.com](mailto:enquiries@fibrelite.com)

**US Office:**

Tel: +1 800 422 2525  
Email: [enquiries@fibrelite.com](mailto:enquiries@fibrelite.com)

**Malaysia Office :**

Tel: + 603 7847 1888  
Email: [enquiries@fibrelite.com](mailto:enquiries@fibrelite.com)